# PRONTO® M51







Versatility comes standard with the **Invacare® Pronto® M51™ Power Wheelchair with Invacare® SureStep® Suspension.** The M51 Wheelchair boasts true center-wheel drive performance for exceptional maneuverability and intuitive driving. The M51 Wheelchair comes standard with a center-post captain's seat with plush contoured foam cushions and vinyl seating surfaces. The M51-R Wheelchair comes with a four-post adjustable rehab seat for consumers with moderate seating and positioning needs. The M51-CG Wheelchair comes with a standard center-of-gravity power tilt system. The patented Invacare SureStep Suspension system provides a smooth ride over transitions and thresholds up to 2" while maintaining stability. The M51 Wheelchair design offers sleek styling and comfort while optimizing maneuverability and accessibility.

#### **Captain's Seat Features**

Medium back captain's seat with flip-up, adjustable width arms

Semi-recline office-style seat with standard flip-up, height and width adjustable arms

Semi-recline captain's seat with standard flip-up, adjustable width arms

Choice of light grey vinyl, charcoal grey vinyl, tan vinyl or grey cloth upholstery 16". 18" and 20" widths

Fully programmable Invacare® MK5™ NX™ Electronics for precise driver control

### Invacare® Formula™ CG Powered **Seating Features**

55° of tilt with 300 lb. weight capacity Starting seat-to-floor height 17.5" (additional options available) Fully programmable Invacare® MK6i™ electronics for maximum function and actuator controls available

#### **Rehab Seat Features**

Standard adjustable ASBA rehab seat can expand in both width and depth Adjustable seat slope

Can be easily retrofitted with a power tilt

Fully programmable Invacare® MK5™ NX™ Electronics for precise driver control

#### HCPCS Code: K0822, K0823, K0835







- 1. True Center-Wheel Drive
- 2. Invacare® SureStep® Suspension
- 3. Optional Invacare Transport Tie-Down\*



\*TRRO includes four factory-installed brackets and wheelchair anchored pelvic belt. TRRO has been crash-tested in accordance with ANSI/RESNA WC Vol 1. Section 19 Frontal Impact Test requirements for wheelchairs with a 168 lbs. crash dummy, which corresponds to a person with a weight of 114 lbs. to 209 lbs. TRBKTS includes four factory-installed wheelchair transport brackets. TRBKTS has not been crash tested in accordance with WC19. Use these transport brackets only to secure an unoccupied wheelchair during transport. As of this date, the Department of Transportation has not approved any tie-down systems for transportation of a user while in a wheelchair, in a moving vehicle of any type. It is Invacare's position that users of wheelchairs should be transferred into appropriate seating in vehicles for transportation and use be made of the restraints available by the auto industry. Invacare cannot and does not recommend any wheelchair transportation systems









Drive

Wheels



Ground

Clearance



Turning

Radius

19.5"



Incline

M51P, M51PR, M51PSR16R/B ₹M51PSR20R/B M51PRSOLID16R/B M51PRSOLIDR/B M51PRSOLID20R/B

Model #

M51-CG



Seat Dimensions 16"-20" W 16"-20" D

Rehab Seat-to-17"-21'

Floor Height\*\*

10.5









Limited

Warranty

add M51PSEMIRED/ M51PSEMIBLUE

Total Weight 198 lb.

Weight Capacity 300 lb.

Motor

2 Pole

Speed 4.25 mph

Maximum

Battery U1

Range Up To 10.5 Miles

Battery

5 Years Base Frame For other seating option specifications refer to the Invacare Visual Configurator. Do not operate on roads, streets or highways.

3 Years Seat Frame 1 Year Electronics/ Motor/Gearbox

## **Invacare Corporation**

www.invacare.com

#### **USA**

One Invacare Way Elyria, Ohio 44035-4190 (800) 333-6900

#### Canada

570 Matheson Blvd. E., Unit 8 Mississauga, Ontario L4Z 4G4 Canada (800) 668 - 5324

©2012 Invacare Corporation. All rights reserved. Trademarks are identified by the symbols <sup>™</sup> and ®. All trademarks are owned by or licensed to Invacare Corporation unless otherwise noted. Specifications are subject to change without notification. Form No. 02-066 Rev. 09/12 120348

